

Torggler

Restoration

ANTISALE

Universal keying agent for protection against saline efflorescence.



- Excellent barrier against all salts
- Water based environment friendly product
- Good water repellent properties
- Ready to use

APPLICATION AREAS

Antisale is used to renovate damp walls, as a primer to prevent efflorescences before application of Intonaco WTA and/or Ekor DP 501. It is highly recommended where the masonry is clearly degraded due to efflorescences

FEATURES

Antisale is a silane-siloxane resin based product in watery dispersion. It is milky white and forms a temporary barrier against all types of salts which form efflorescences in buildings and which are diffused by rising water. The silane-siloxane resins ensure capillary water-proofing and prevent the diffusion of salt containing water. Therefore, the salts cannot penetrate the fresh Intonaco WTA.

The advantages of Antisale are the following:

- Safe to use and environment friendly, because it is a water-based product which does not contain organic solvents and/or toxic substances.
- Easy and rapid to use, because only one coat of one product is required without diluting.
- Variety of uses, because it can be used for all types of efflorescences (Chlorides, Sulphates and even Nitrates).

WARNINGS

Do NOT apply at temperatures below +5 °C.

INSTRUCTIONS FOR USE

Remove all friable loose parts from the degraded wall until the firm and solid background is bared. Wash the background with a water jet and let it dry. Shake the Antisale well in its can. Apply one thick coat, preferably with a spray pump. Wait at least 24 hours before applying the plaster (follow the instructions in the technical data sheet). In case of high dampness in the wall and/or in the environment, wait at least 3 days.

TECHNICAL SPECIFICATIONS

Colour	white liquid
Density	0,995 kg/l
pH	7-8
Dry substance	approx. 5,5%
Drying time	approx. 24 hours
Packaging	canister
Packaging size	10 l, 10 l, 5 l, 5 l
Pallet	128 canisters, 60 canisters

CONSUMPTION

Depending on the porosity and smoothness of the background, consumption ranges from 0.3 to 0.5 litres/m².

STORAGE

Antisale must be stored in a dry and cool area, away from the sun. It must be protected from frost. If closed in the original packaging, it can be stored for at least 12 months.

The information contained in this document is reported on the basis of our experience and knowledge; therefore, any recommendations and suggestions made are without any guarantee and must be verified before using the product by those who intend to use it, who assume all responsibility that may result from its use since the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. Torggler reserves the right to modify, replace and/or delete the items, as well as to change the product data in this document without prior notice; in this case the indications given here may no longer be valid. Always refer to the latest version of the data sheet, available at www.torggler.com. Version 23.11.2021.