

Torggler

Waterproofing

SHOWER TAPE

Self-adhesive shower/bathtub connection tape.



- For tub/shower tray
- Self-adhesive
- Easy to apply
- For wet and damp areas
- Alkali-resistant
- Complies with DIN 18534



APPLICATION AREAS

Waterproof, flexible, fleece-coated double-sided sealing tape with a self-adhesive layer for shower tray and bathtub fittings made of plastic and sheet steel.

FEATURES

Self-adhesive shower/bathtub connection tape.

WARNINGS

Store the product at temperatures between +5 °C and +40 °C. Temperatures above +28 °C may make it difficult to peel off the protective film. Protect against UV radiation.

INSTRUCTIONS FOR USE

Clean and degrease the tub edge with suitable cleaning agents (e.g. Acetone). Bond the self-adhesive part of the Shower Tape 120 mm-10 m sealing tape firmly to the edge of the tub so that the tape remains facing upwards. Place the tape in one piece, do not use leftovers. Position the tub or shower tray. Glue the sealing tape to the wall

with a waterproofer like Flex 2K, Flexistar or Aquatech. The joints of the sealing tape must overlap by at least 6 mm.

TECHNICAL SPECIFICATIONS

Parameter	Value
Material composition	Carrier : PP Coating : thermoplastic elastomer, weather-resistant
Tape width	120 mm
Tape length	10 m
Weight	60 g/m ²
Thickness	0,7 mm
Temperature resistance	min. -5 °C / max. +60 °C

Color	Grey
Dimensions	120 mm
Packaging size	10 m
Pallet	500 rolls

STORAGE

The material must be stored in a dry, covered room at a temperature between +5 and +40 °C. Temperatures above 50 °C can lead to difficulties in peeling off the silicone protection film. The properties of Shower Tape 120 mm-10 m remain unchanged for a very long time. However, we recommend using it within 12 months of production. Protect from UV exposure.

CERTIFICATIONS

Shower Tape 120 mm-10 m is certified as A+ by the Eurofins organisation.

The information contained in this document is reported on the basis of our experience and knowledge; therefore, any recommendations and suggestions made are without any guarantee and must be verified before using the product by those who intend to use it, who assume all responsibility that may result from its use since the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. Torggler reserves the right to modify, replace and/or delete the items, as well as to change the product data in this document without prior notice; in this case the indications given here may no longer be valid. Always refer to the latest version of the data sheet, available at www.torggler.com. Version 22.05.2024.