Torggler

Restoration

GP 100

Ready-to-use paste putty for indoor use.



APPLICATION AREAS

GP 100 is suitable for:

- Render of masonry or plasterboard surfaces
- The treatment of walls and ceilings made of gypsum, concrete or plaster or cement-lime mortars even if in the raw state.

FEATURES

GP 100 is a ready-to-use paste putty for indoor use ideal for rendering masonry or plasterboard surfaces, suitable for the treatment of walls and floors made of gypsum, concrete or plaster or cement-lime mortars, even if in its raw state.

WARNINGS

- Do not add other materials to the ready product.
- Do not apply GP 100 at temperatures below +5 °C. Store the product in a dry place, away from heat and frost.
- Paints and coatings must be applied when the product is completely dry.

INSTRUCTIONS FOR USE

Preparation for use

Thoroughly clean the surface to be treated by completely removing any residue of dust, grease and efflorescence.

Instructions for use

Load the trowel with GP 100 and apply it to the surface. In case of high thickness (over 1.5 mm) it is recommended to fill the surface with several subsequent applications. Paints and coatings must be applied when the product is completely dry.

It is recommended to close the package carefully after partial use and be careful not to pollute the unused product with dry residues or uncleaned tools.

TECHNICAL SPECIFICATIONS

Appearance	Pasty
Color	White
Packaging	bucket
Packaging size	20kg, 5 kg
Pallet	120 buckets, 44 buckets

CONSUMPTION

The consumption of **GP 100** is approx. $14 \text{ kg/m}^2/\text{cm}$.

STORAGE

Store GP 100 in a dry place protected from heat and frost. It will keep for at least 12 months in the original unopened packaging. **PROTECT FROM HUMIDITY**.

The information contained in this document is reported on the basis of our experience and knowledge; therefore, any recommendations and suggestions made are without any guarantee and must be verified before using the product by those who intend to use it, who assume all responsibility that may result from its use since the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. Torggler reserves the right to modify, replace and/or delete the items, as well as to change the product data in this document without prior notice; in this case the indications given here may no longer be valid. Always refer to the latest version of the data sheet, available at www.torggler.com. Version 11.02.2021.