

Torggler

Sealants and Adhesives

SMOOTH

Neutral smoothing agent based on amphoteric surfactants in aqueous solution, for professional surface finishing of connection joints and expansion joints made with silicone, acrylic and hybrid sealants.



- Ready to use
- Suitable for all types of sealants
- Improves the finish of joints
- Does not trigger microbiological growth

APPLICATION AREAS

Packaged in a practical spray bottle with vaporizer, Smooth is ready to use and does not require further dilution. It is compatible with acrylic, silicone and hybrid sealants and can be used regardless of the chemical nature of the product used to make the joints between the different elements.

Once applied, it accelerates the surface cross-linking and promotes the uniform hardening of the sealant mass. Compared to traditional smoothing with diluted soaps or detergents, the use of Smooth is preferable because it is chemically less aggressive towards the components of the various types of sealants.

WARNINGS

- Do not apply at temperatures below 0 °C.
- Make sure of the sealants surface crosslinking time to avoid tearing the already hardened surface.
- Avoid build-up of smoothing agent on horizontal joints to prevent staining.
- Do not use on crystal clear hybrid sealants.
- pH 7.5-8.5

INSTRUCTIONS FOR USE

Preparation for use

The sides of the joint must be solid, clean, degreased and consistent. Place self-adhesive paper tape along the edges and inject an excess amount of sealant.

Instructions for use

Smooth out with a spatula moistened with Smooth smoothing agent before the surface filming begins: depending on the type of sealant, temperature and air humidity, the time interval can vary considerably. Apply a certain pressure in order to obtain a void-free filling and complete adhesion of the sealant on the sides of the joint. Remove the protective tape immediately, lightly spray Smooth and rub the surface with your fingers to level out any peaks or excesses.

Especially in the case of silicone sealing made on porous/absorbent substrates, it is recommended to remove the smoothing agent residues with water immediately after smoothing.

TECHNICAL SPECIFICATIONS

Color	Transparent
Packaging	bottle
Packaging size	8x750 ml
Pallet	46 cardboards

CONSUMPTION

Depending on the laying technique: approx. 0.3 l/m²

STORAGE

Store in a dry place, protected from frost and heat. In the original packaging it is kept for at least 24 months.

The information contained in this document is reported on the basis of our experience and knowledge; therefore, any recommendations and suggestions made are without any guarantee and must be verified before using the product by those who intend to use it, who assume all responsibility that may result from its use since the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. Torggler reserves the right to modify, replace and/or delete the items, as well as to change the product data in this document without prior notice; in this case the indications given here may no longer be valid. Always refer to the latest version of the data sheet, available at www.torggler.com. Version 11.02.2021.