

Torggler

Polyurethane Foams

CLEANER FOR POLYURETHANE FOAMS

Spray cleaner for fresh polyurethane foam of any type and sealants.



- Easy application
- Fast action without residues
- Dual use: with gun or by means of the dispenser button
- Excellent for both gun and manual foam cans
- Allows multiple use of cans

APPLICATION AREAS

Rapid removal of polyurethane foam not yet hardened from any soiled surface. Professional cleaning of foam dispensing guns, immediately after extrusion. The Cleaner for polyurethane foam does not dissolve the hardened foam even after prolonged action: in this case it can only be removed mechanically with a spatula or sandpaper.

FEATURES

Cleaner for polyurethane foam consists of a mixture of solvents and polymers and a propellant based on denatured, odourless and non-toxic hydrocarbons. It is a transparent liquid capable of rapidly dissolving fresh polyurethane foam. It does not melt hardened foam.

WARNINGS

Attention! Cleaner for polyurethane foam can dissolve or discolour the surfaces on which it is applied (paint, colour, synthetic materials, fabrics, etc.) so, before use, always make a test in a hidden place to make sure that the substrate doesn't get damaged.

INSTRUCTIONS FOR USE

To remove the polyurethane foam from the extrusion gun, screw the cylinder, without forcing it, into the appropriate circular threaded coupling. Push the trigger to let the residue foam come out from the gun. As soon as the solvent comes out, release the trigger and wait 1 or 2 minutes for the solvent to dissolve the residues inside the gun. Then, by pressing the trigger, discharge into a suitable container until pure solvent comes out. If necessary repeat the operation 2 or 3 times. Unscrew the clean cylinder of the gun so that it will be ready for a new use. If the gun is not immediately reused, close the rear valve. To remove foam from contaminated surfaces, fit the spray nozzle button on the cylinder valve and press. If necessary repeat the application of the solvent several times using absorbent paper to help.

TECHNICAL SPECIFICATIONS

Packaging	can
Packaging size	12 x 500ml

STORAGE

Cleaner for polyurethane foams must be stored in an upright position at a temperature of +5/+30 °C. Under these conditions the storage stability is at least 36 months. Cylinders that are not completely used can be stored for about 6 months if closed tightly.

LIST OF INGREDIENTS

Aliphatic hydrocarbons	15% < 30%
------------------------	-----------

The information contained in this document is reported on the basis of our experience and knowledge; therefore, any recommendations and suggestions made are without any guarantee and must be verified before using the product by those who intend to use it, who assume all responsibility that may result from its use since the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. Torggler reserves the right to modify, replace and/or delete the items, as well as to change the product data in this document without prior notice; in this case the indications given here may no longer be valid. Always refer to the latest version of the data sheet, available at www.torggler.com. Version 09.02.2021.